Chain actuator PA-K-50/600



Technical Data

Input voltage	24 V DC
Nominal current	1.4
Running speed	11
IP code	IP32
Switch on duration	30

MOUNTING POSITIONS



TECHNICAL DATA

Matchcode	PA-K-50/600
Article name	Chain actuator PA-K-50/600
Part number	M2 2232
Input voltage	24 V DC
Nominal current	1.4
Input voltage range	- 15 % / + 15 %
Networked standby	0.9 W (1 min)
Stroke	600
Push force	500
Pull force	500
Nominal locking force	< 3000 N
Cut-Off	Integrated electronic overload cut-off
Running speed	11
IP code	IP32
Switch on duration	30
Mounting way	aufgesetzt
Weight	2.10
Housing	Aluminium profile housing EV1 anodized
Housing type	Aluminium
Colour	On request
Housing length	622
Housing width	50
Housing height	41
Appliance class	III
Connection cable	SICO PLUG connection. Excluding connection cable / set.
Nominal working temperature	20
Environment temperature range	-5 °C - 75 °C

Chain actuator PA-K-50/600

Brackets included	nein
Customs tariff no	84798997
Packaging part no.	N-99-188

ACCESSORIES

Part no.	Matchcode
K2 5088	K-K50-SKI
K2 5089	K-K50-OK
K2 5090	K-K50-AKI
K2 5092	K-K50-A
K2 5093	K-K50-K
K2 5094	K-K50-FLEX
K2 5106	K-K-OK-SK
SD1 8513	SICO-LINK-USB-110
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER